



NATIONAL DECLARATION OF PERFORMANCE

No. 13/2017



2011

- 1. The name and trade name of the construction product:**
Bathroom point inlet
- 2. The designation of the type of the construction product:**
AQUA AMBIENT CLASSIC bathroom point inlet with ARCO, SPOT, CUBE, ORIENT grates
- 3. Intended use or uses:**
AQUA AMBIENT CLASSIC inlets are used for disposal of sewage from a shower head in areas without vehicular traffic, for example bathrooms in apartments, nursing homes, hotels, schools, public baths, terraces and roofs with greenery.
- 4. Name and address of the manufacturer and the place of manufacture of the product:**
CAPRICORN S.A.
58-160 Świebodzice
Ciernie 11
- 5. Name and address of the authorized representative, as long as it was established:**
not applicable.
- 6. National system of assessment and verification of permanent performance characteristics:**
system 4.
- 7. National technical specification:**
Polish product standard:
EN 1253-1:2015 - Gullies for buildings - Part 1: Requirements Floor manholes with flap sealing at a depth of at least 50 mm.
The name of the accredited laboratory and accreditation number:
„GAMRAT” Spółka Akcyjna, Centrum Jakość
38-200 Jasło, ul. Mickiewicza 108
Accreditation number: AB 237

Capricorn S.A.
Ciernie 11, 58-160 Świebodzice

Biuro Zarządu
sekretariat@capricorn.pl
tel. +48 74 854 05 16
fax +48 71 722 28 18

Dział Eksportu
sales@capricorn.pl
tel. +48 74 8503 546

Sprzedaż krajowa
zamowienia@capricorn.pl
tel. +48 74 8503 528
+48 74 8503 551
fax +48 74 85 03 535

www.capricorn.pl

NIP: 884-002-16-00, Regon: 891489258
Sąd rejonowy dla Wrocławia-Fabryczna we Wrocławiu
IX Wydział Gospodarczy KRS: 0000472600,
Wysokość kapitału zakładowego: 400 tys. PLN

ALIOR BANK S.A SWIFT (BIC) ALBPPLPW
IBAN: PL49 1060 0076 0000 3210 0015 3728 (WALUTA PLN)
IBAN: PL65 1060 0076 0000 3210 0015 3731 (WALUTA EUR)
IBAN: PL95 1060 0076 0000 3210 0015 3773 (WALUTA USD)


8. Declared performance:

The essential characteristics of the product for the intended use or uses:	Declared performance:	Comments
The position of the side inlet - affects grooving with the side discharge	T1	-
Temperature cycling	Class A - application anywhere in the fitting	-
Resistance to waste waters with periodic temperature 95°C	Meets the requirements	-
Load resistance	Class H1,5 – strength of 150 kg	-
Throughput	≥ 0.8l/s	-
Dimensions	Meets the requirements	-
Water seal height ≥ 50 mm	Meets the requirements	-
Resistance to the water seal for vacuum ≥400 Pa	Meets the requirements	-
Self-cleansing capacity	Meets the requirements	-
Preventing of congestion	Meets the requirements	-
Odor tightness	Meets the requirements	-
Water tightness of body	Meets the requirements	-

9. The performance of the product identified above are compatible with all declared performances listed in section 8. This national declaration of commercial properties shall be delivered in accordance with the law of 16 April 2004 on the construction product, with the sole responsibility of the manufacturer.

10. The concentration of the substance referred to in Article 31 or Article 33 of Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18 December 2006 does not exceed in an article 0.1% by weight.

On behalf of the producer signed by:

Monika Piekarz
 Director of Quality and Deployments



.....
 (Signature)

Świebodzice, 2.01.2017
 (Place and date of issue)

