

NATIONAL DECLARATION OF PERFORMANCE

No. 02/2019



- 1. The name and trade name of the construction product:**
Handles
- 2. The designation of the type of the construction product:**
series A handles,
series E handles,
series F handles,
single arm handles,
double arm handles.
- 3. Intended use or uses:**
Plastic handles CAPRICORN are designed to attach pipes made of plastic, copper and steel or made of other materials with an outer diameter of 8 to 35 mm indoor.
- 4. Nazwa i adres siedziby producenta oraz miejsce produkcji wyrobu:**
CAPRICORN S.A.
58-160 Świebodzice
Ciernie 11
- 5. Name and address of the authorized representative, as long as it was established:**
not applicable.
- 6. National system of assessment and verification of permanent performance characteristics:**
system 3.
- 7. National technical specification:**
National Technical Assessment:
National Technical Assessment ITB-KOT-2019/1138 - Capricorn plastic handles for installation pipes.
The technical assessment unit/ The National Unit of technical assessment:
Instytut Techniki Budowlanej

Capricorn S.A.
Ciernie 11, 58-160 Świebodzice

www.capricorn.pl

NIP: 884-002-16-00, Regon: 891489258
Sąd rejonowy dla Wrocławia-Fabryczna we Wrocławiu
IX Wydział Gospodarczy KRS: 0000472600,
Wysokość kapitału zakładowego: 400 tys. PLN

Biuro Zarządu
sekretariat@capricorn.pl
tel. +48 74 854 05 16
fax +48 71 722 28 18

Dział Eksportu
sales@capricorn.pl
tel. +48 74 8503 546

Sprzedaż krajowa
zamowienia@capricorn.pl
tel. +48 74 8503 528
+48 74 8503 551

fax +48 74 85 03 535

ALIOR BANK S.A SWIFT (BIC) ALBPPLPW
IBAN: PL49 1060 0076 0000 3210 0015 3728 (WALUTA PLN)
IBAN: PL65 1060 0076 0000 3210 0015 3731 (WALUTA EUR)
IBAN: PL95 1060 0076 0000 3210 0015 3773 (WALUTA USD)


PL 00-611 Warszawa
 ul. Filtrowa 1

8. Declared performance:

The essential characteristics of the product for the intended use or uses:	Declared performance:	Comments
Vicat softening point	PP ≥ 65°C PA ≥ 190°C	Detailed information in National Technical Assessment ITB-KOT-2019/1138
Pull-out strength of the pipe holders:	≥43 N	
Characteristic bearing capacity of single and double arm fastening holders with pins with a diameter of 9 mm to pulling out from their base ✓ Class C 16/20 Concrete ✓ Class 3 Cellular Concrete ✓ Class 15 Solid Ceramic Brick ✓ Class 15 Hollow Ceramic Brick	PP ≥ 118 N PA ≥ 122 N	
Characteristic bearing capacity of single and double arm fastening holders with pins with a diameter of 11 mm to pulling out from their base ✓ Class C 16/20 Concrete ✓ Class 3 Cellular Concrete ✓ Class 15 Solid Ceramic Brick ✓ Class 15 Hollow Ceramic Brick	PP ≥ 129 N PA ≥ 131 N	

9. The performance of the product identified above are compatible with all declared performances listed in section 8. This national declaration of commercial properties shall be delivered in accordance with the law of 16 April 2004 on the construction product, with the sole responsibility of the manufacturer.

10. The concentration of the substance referred to in Article 31 or Article 33 of Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18 December 2006 does not exceed in an article 0.1% by weight.



On behalf of the producer signed by:

Monika Piekarz
Member of the Board for Production

Świebodzice, 28.10.2019
(Place and date of issue)

CAPRICORN S.A.
Członek Zarządu ds. Produkcji

.....Monika Piekarz.....

(Signature)

Capricorn S.A.
Ciernie 11, 58-160 Świebodzice

Biuro Zarządu
sekretariat@capricorn.pl
tel. +48 74 854 05 16
fax +48 71 722 28 18

Dział Eksportu
sales@capricorn.pl
tel. +48 74 8503 546

Sprzedaż krajowa
zamowienia@capricorn.pl
tel. +48 74 8503 528
+48 74 8503 551

fax +48 74 85 03 535

www.capricorn.pl

NIP: 884-002-16-00, Regon: 891489258
Sąd rejonowy dla Wrocławia-Fabryczna we Wrocławiu
IX Wydział Gospodarczy KRS: 0000472600,
Wysokość kapitału zakładowego: 400 tys. PLN

ALIOR BANK S.A SWIFT (BIC) ALBPPLPW
IBAN: PL49 1060 0076 0000 3210 0015 3728 (WALUTA PLN)
IBAN: PL65 1060 0076 0000 3210 0015 3731 (WALUTA EUR)
IBAN: PL95 1060 0076 0000 3210 0015 3773 (WALUTA USD)

